


DIN 2211 Standartlarında V Kasnak Kanalı Ölçüleri



TİP / TYPES	Y	Z	A	B	C	D	E
V KAYIŞ/V BELT	6	10	13	17	22	32	38
b1	6,3	9,7	12,7	16,3	22	32,7	38,7
C	1,6	2	2,8	3,5	4,8	8,1	9,6
E	8	12	15	19	25,5	37	44,5
F	6	8	10	12,5	17	24	29
T Min.	7,9	11	14	18	24	33	38
$\alpha=32^\circ$	DW<60						
$\alpha=34^\circ$		DW≤80	DW≤118	DW≤190	DW≤315		
$\alpha=36^\circ$	DW>60					DW≤475	DW≤475
$\alpha=38^\circ$		DW≥80	DW≥118	DW≥190	DW≥315	DW≥475	DW≥475

KASNAK SAYISI VE TİPE GÖRE b2 GENİ

n	y	z	A	B	C	D	E
1	12	16	20	25	34	46	56
2	20	28	35	44	59,5	83	100,5
3	28	40	50	63	85	120	145
4	36	52	65	82	110,5	157	189,5
5	0	64	80	101	136	194	234
6	0	76	95	120	161,5	231	278,5
8	0	0	0	158	212,5	305	367,5
10	0	0	0	196	263,5	379	456,5
12	0	0	0	234	314,5	543	545,5
14	0	0	0	272	365,5	527	634,5
16	0	0	0	310	416,5	601	723,5
18	0	0	0	348	467,5	675	812,5